



V450 | HomeMaker Series

Egress by Min Width or Min Height

Operation	Minimum Width		Minimum Height	
	Width (in)	Height (in)	Width (in)	Height (in)
Single Hung	31	71.5	38.5	58
2 Lite Slider	47.5	47.5	78.5	28.25
3-Lite Slider - 1/4 - 1/2 - 1/4	96.75	45.375	120	36
Casement w/Standard Hardware	31.75	46.75	42	33
Casement w/Egress Hardware	26.75	46.75	42	29.625

* with Egress Hardware ***with a 60 bottom sash

Nominal Size	Exact Dimensions	Casement	Single Hung	Slider	XOX
2440	27-1/2 x 47-1/2	X*			
2450	27-1/2 x 59-1/2	X*			
2460	27-1/2 x 71-1/2	X*			
2640	29-1/2 x 47-1/2	X*			
2650	29-1/2 x 59-1/2	X*			
2660	29-1/2 x 71-1/2	X*			
3040	35-1/2 x 47-1/2	X			
3050	35-1/2 x 59-1/2	X			
3051	35-1/2 x 60-1/2	X	X		
3056	35-1/2 x 65-1/2	X	X		
3060	35-1/2 x 71-1/2	X	X		
3070	35-1/2 x 83-1/2		X***		
3080	35-1/2 x 95-1/2		X***		
3650	41-1/2 x 59-1/2		X		
3656	41-1/2 x 65-1/2		X		
3660	41-1/2 x 71-1/2		X		
4040	47-1/2 x 47-1/2			X	
4050	47-1/2 x 59-1/2		X	X	
4056	47-1/2 x 65-1/2		X	X	
4060	47-1/2 x 71-1/2		X	X	
	50.00 x 47-1/2			X	
4640	53-1/2 x 47-1/2			X	
5036	59-1/2 x 41-1/2			X	
5040	59-1/2 x 47-1/2			X	
5046	59-1/2 x 53-1/2			X	
6030	71-1/2 x 35-1/2			X	
8040	95-1/2 x 47-1/2				X
8050	95-1/2 x 59-1/2				X
8060	95-1/2 x 71-1/2				X
10030	119-1/2 x 35-1/2				X

Note: Units with 1/4" glass may require limited travel balances, which could affect egress sizing

An egress window must satisfy the following International Residential Code (IRC) criteria:

1. Minimum width opening - 20"
2. Minimum height opening - 24"
3. Minimum net clear opening, ground floor - 5.0 sq ft
4. Minimum net clear opening, all other floors - 5.7 sq ft
5. Maximum latch height above floor - 54 inches
6. Maximum sill height above floor - 44 inches

Please check and follow your local building code requirements, as they may differ.