

Operating Style	Model	Tested Size	Performance Rating	Air Infiltration (cfm/ft ²)	Water Performance (psf)	Report Number
Horizontal Slider						
Half Vent	HV	72 x 72	PG30	0.05	4.59	m2934.01-901-47-r2
Double Vent	DV	144 x 72	PG20	0.10	5.43	I5622.01-901-47
Vertical Slider						
Single Hung	SH	57 x 92	PG30	0.03	4.60	I5622.01-901-47
Picture Window						
Picture Window	PW	96 x 72	PG30	0.01	4.60	m1728.01-901-47
Slider Frame PW	PWR	84 x 72	PG20	0.03	3.13	310-7567
Slider Frame PW	PWR	72 x 72	PG30	0.02	5.43	Q9170.01-901-47
Fixed Sash PW (Case/Awn Frame)	CAF	96 x 72	PG20	0.02	3.13	m1731.01-901-47
Casement						
Full Casement	FC	36 x 60	PG35	0.03	5.43	I5714.01-901-47-r1
Awning						
Full Awning	FA	60 x 36	PG35	0.01	6.89	310-3547
Sliding Patio Door						
Two Panel (XO/OX)	SD2	95.5 x 95.5	PG30	0.16	4.50	S2009-681
Three Panel (XOO/OOX)	SD3	141.5 x 95.5	PG20	0.23	4.50	NS2009-717
Three Panel (OXO)	SD3	141.5 x 95.5	PG20	0.19	3.75	NS2009-718
Four Panel (OXXO)	SD4	189.5 x 95.5	PG20	0.07	3.00	NS2009-719
Inswing Patio Door						
One Panel (X)	IS1P1	36.5 x 95.5	PG25	0.03	3.75	310-1205
Two Panel (XX)	IS2P2	71.5 x 95.5	PG25	0.03	3.75	310-1205
XXXX Operable Sidelites	IS4P2S	123.5 x 95.5	PG25	0.03	3.75	310-1205
OXXO Fixed Sidelites	IS4P2S	123.5 x 95.5	PG25	0.05	3.75	310-1212
Outswing Patio Door						
One Panel (X)	OS1P1	36.5 x 95.5	PG25	0.13	3.75	310-1227
Two Panel (XX)	OS2P2	71.5 x 95.5	PG25	0.13	3.75	310-1227
XXXX Operable Sidelites	OS4P2S	123.5 x 95.5	PG25	0.13	3.75	310-1227
OXXO Fixed Sidelites	OS4P2S	123.5 x 95.5	PG30	0.10	4.50	310-1236